

A GLOBAL PROVIDER OF ENHANCED THERMAL CUTTING SOLUTIONS

EX-TRACK® PA-1

SOPHISTICATED PORTABLE PIPE CUTTING SYSTEM

EX-TRACK®PA-1 is a portable cutting system designed for cutting mild steel tubes using an oxy-fuel torch. With this device you can cut pipes up to 600 mm diameter (with included chain) and with wall thicknesses up to 90 mm and manually control the whole cutting process - no electricity needed. PA-1 is a handy cutting tool for use on construction sites, and in workshops, where it is necessary to cut tubes, make a bevel, etc. A flashback arrestor protects the device from damage. After installation of two larger wheels (included in the package), you can even cut tubes with diameters smaller than 108 mm. Just swap the wheels. The clutch leveler allows you to quickly move the device onto the desired cutting spot. Cutting tubes with EX-TRACK® PA-1 is much faster than cutting with a standard grinder and the cut surface is much smoother. The whole device is easy to assemble and it's easy to use. Oxy-fuel consumables starter kit and basic assembly tools are included as well.



Steel plants



Structural



General
fabrication



Training and
education



Craft hobby and
non industrial users

JUST MOUNT IT AND CUT PIPES!




THERMACUT®
THE CUTTING COMPANY®

THERMACUT®, THE CUTTING COMPANY®, FHT-EX®, EX-TRAFIRE®, EX-TRACK®, EX-TRABEAM® AND EX-TRAFIAME® ARE REGISTERED TRADEMARKS OF THERMACUT, K.S. AND MAY BE REGISTERED IN CZECH REPUBLIC AND/OR OTHER COUNTRIES. ALL OTHER TRADEMARKS ARE PROPERTIES OF THEIR RESPECTIVE OWNERS. MOST THERMACUT® PARTS ARE MADE FOR OR BY AN IBG COMPANY. PARTS INDICATED WITH A OEM ARE ORIGINAL PARTS MANUFACTURED BY THE ABOVE NAMED MANUFACTURER AND ARE BEING RESOLD BY THERMACUT®. THERMACUT® RESERVES THE RIGHT TO SUBSTITUTE OEM PARTS IN PLACE OF THERMACUT® PARTS. VALID FROM MARCH 2023 • PREVIOUS VERSION IS NO LONGER VALID. • © COPYRIGHT 2023 BY THERMACUT® CZECH REPUBLIC. ALL RIGHTS RESERVED.

WWW.THERMACUT.COM
EXTRACK@THERMACUT.CZ

EX-TRACK® PA-1
package content

- EX-TRACK® PA-1 device body
- Gas distributor including hoses and torch assembly
- Tip for propane (3 pcs - type 1, 2, 3)
- Open wrenches (2 pcs)
- Consumables cleaning toolkit (needles)
- Gas fittings
- Horizontal torch holder
- Vertical torch holder
- Chain (80 links)
- Operator manual
- Larger wheels (2 pcs)



EX-TRACK® PA-1
specifications

Whole package weight [kg]	12
Device dimensions [mm]	325 x 325 x 425
Type of application	oxy-fuel cutting
Type of operation	manual
Effective pipe cutting diameter [mm] *	108-600
Chain links	80
Material thickness [mm]	5-90
Groove shape	I-shape V-bevel

Range of vertical torch movement [mm]	50
Range of lateral torch movement [mm]	100
Permissible fuel gas	Propane
Max. gas inlet pressure	Propane - up to 3 bar / 43.5 PSI Oxygen - up to 10 bar / 145 PSI

AMBIENT CONDITIONS FOR TRANSPORT AND STORAGE

Ambient temperature	-20 °C to +55 °C
Relative humidity	< 50 % @ +40 °C < 90 % @ +20 °C

* After the installation of two larger wheels it is possible to cut pipes with a diameter of 80-108 mm.

Ordering info

Description	Quantity	Part. No.
EX-TRACK® PA-1/CE/1-OXY/pipe cutter	1	EX-0-704-005
Cutting tip propane 00 (1-5mm)	1	EX-0-708-017
Cutting tip propane 0 (5-10mm)	1	EX-0-708-018
Cutting tip propane 1 (10-20mm)	1	EX-0-708-019
Cutting tip propane 2 (20-35mm)	1	EX-0-708-020
Cutting tip propane 3 (35-60mm)	1	EX-0-708-021
Cutting tip propane 4 (60-90mm)	1	EX-0-708-022